



The Light Field

Electromagnetic waves; photons

Frequency spectra
and color



From London and Upton

Polarization

Spatial distribution

CS348B Lecture 4

Pat Hanrahan, Spring 2000

Questions

1. How is light measured?
2. How is the spatial distribution of light energy described?
3. How is reflection from a surface characterized?
4. What are the conditions for equilibrium flow of light in an environment?

CS348B Lecture 4

Pat Hanrahan, Spring 2000

Transport Theory

Transport theory is concerned with calculating how stuff Q flows in the environment.


- Mass m
- Charge q
- Radiant energy F

Transport quantities are built around a core of basic geometric ideas. These are tricky!

The easiest way to learn transport theory is to think in terms of particles (photons).

Particle Density

Phase Space

Particle characterized by position and velocity 


Particle densities

Ratio of number of particles to volumes (phase space)

$$\boxed{d^3x} \times \boxed{d^3v} \quad n(x, v, t) = \lim_{\Delta^3x \Delta^3v \rightarrow 0} \frac{N(t)}{\Delta^3x \Delta^3v}$$
$$\mathcal{R}^3 \times \mathcal{R}^3$$

Flows

Count particles crossing a surface



$$d^3x = v \cos \mathbf{q} dA = (\vec{v} dt) \cdot d\vec{A}$$

$$Q(x, v) = n(x, v) d^3x = n(x, v) (\vec{v} dt) \cdot d\vec{A}$$

■ Flux [Stuff/Time] (or Rate or Flow)

$$\Phi = \frac{dQ}{dt} = n(x, v) \vec{v} \cdot d\vec{A}$$

■ Flux density [Stuff/(Time • Area)]

$$\Phi = \frac{d^2Q}{dt dA} = n(x, v) \vec{v} \cdot d\hat{A} = n(x, v) v \cos \mathbf{q}$$

CS348B Lecture 4

Pat Hanrahan, Spring 2000


Angles and Solid Angles

■ Angle $\mathbf{q} = \frac{\text{length}}{\text{radius}}$

⊢ circle has 2π radians

■ Solid angle $\Omega = \frac{\text{area}}{\text{radius}^2}$

⊢ sphere has 4π steradians




If the area is not on the sphere, then the solid angle subtended by the area is equal to the area projected onto the unit sphere.

CS348B Lecture 4

Pat Hanrahan, Spring 2000

Differential Solid Angles



$$dA = (r dq)(r \sin q d\phi) \\ = r^2 \sin q dq d\phi$$

$$d\omega = \frac{dA}{r^2} = \sin q dq d\phi$$


$$S = \int_0^{\pi} \int_0^{2\pi} \sin q dq d\phi = 4\pi$$

CS348B Lecture 4

Pat Hanrahan, Spring 2000

Radiance and Luminance

Definition: The *radiance* (*luminance*) is the power per unit projected area perpendicular to the ray per unit solid angle in the direction of the ray.




$$L(x, \omega) = \frac{d^2\Phi}{d\vec{\omega} \cdot d\vec{A}}$$

$$d^2\Phi = L(x, \omega) d\vec{\omega} \cdot d\vec{A} \\ = L(x, \omega) \cos q d\omega dA$$

CS348B Lecture 4

Pat Hanrahan, Spring 2000


Environment Maps



Gazing Ball
Photograph by P. Haeberli



180 degree fisheye
Photograph by R. Packo




Cubical Environment Map

CS348B Lecture 4

Pat Hanrahan, Spring 2000

Spherical Light Field




Capture all the light leaving
an object - like a hologram




CS348B Lecture 4

Pat Hanrahan, Spring 2000

Two-Plane Light Field



2D Array of Cameras



2D Array of Images


CS348B Lecture 4

Pat Hanrahan, Spring 2000

Radiant Energy and Power

Power: Watts vs. Lumen

- Energy efficiency
- Spectral efficacy



Energy: Joules vs. Talbot

- Since the velocity of light is so fast, may typically ignore distinction between power and energy
- Exposure - Reaction rates
 - Film response
 - Skin - sunburn

CS348B Lecture 4

Pat Hanrahan, Spring 2000

Radiometry vs. Photometry

- Radiance and Radiometry [Units = Watts]

Physical measurement of electromagnetic energy.

- Luminance and Photometry [Units = Lumen]

Perceptual measurement of relative subjective sensation due to light of different wavelengths.

- Brightness [Units = Brils]


Perceptual measurement of the relative perceived sensation of light of different intensities.

Properties of Radiance

1. Fundamental field quantity that characterizes the distribution of light in an environment.
 - All other quantities are derived from it.
2. Radiance invariant along a ray.
 - Energy and throughput conserved implies radiance conserved.
3. Response of a sensor proportional to radiance.

Radiance: 1st Law

The radiance in the direction of a light ray remains constant as the ray propagates.



L is the numeric quantity that should be associated with rays in ray tracers.


CS348B Lecture 4

Pat Hanrahan, Spring 2000

Radiance: 2nd Law

The response of a sensor is proportional to the radiance of the surface visible to the sensor.

L is what should be computed and displayed.



$$R = \iint_{A \Omega} L \cos \mathbf{q} \, d\omega \, dA = L \iint_{A \Omega} \cos \mathbf{q} \, d\omega \, dA = LT$$

Throughput $T = \iint_{A \Omega} \cos \mathbf{q} \, d\omega \, dA$



CS348B Lecture 4

Pat Hanrahan, Spring 2000

Quiz 1

Does radiance increase under a magnifying glass?

NO!!




CS348B Lecture 4

Pat Hanrahan, Spring 2000

Quiz 2

Does the brightness that a wall appears to the eye depend on the distance of the viewer to the wall?

NO!!



CS348B Lecture 4

Pat Hanrahan, Spring 2000